

## ISO/IEC 15693 Protocol HF Tag Reader



HF  
Reader

Model : SID-H937-SRIP

Size : 123mmx94mmx29mm

Weight : 144g

## GENERAL DESCRIPTION


SID-H937-SRIP is a high performance ISO/IEC15693 protocol HF tag reader. It is designed upon fully self-intellectual property and supports fast tag read/write operation with high identification rate. It can be widely applied in many RFID application systems such as personnel identification, conference attendance system, access control, anti-counterfeit and industrial production process control system.

## FEATURES

- Self-intellectual property;
- Support mainstream ISO/IEC15693 protocol tag (TI, PHILIPS, ST, INFINEON, FUJITSU, EM...);
- Advanced tag processing algorithm, high identification rate;
- Built-in TX/RX antenna with effective distance up to 100mm<sup>\*</sup>;
- Support Scan-mode<sup>①</sup>;
- Low power dissipation design with single DC+12V power source needed;
- Support TCP/IP and RS232 interface and provide DLL and demonstration software to facilitate development;
- Provide DLL and demonstration software to facilitate development.

<sup>①</sup>Scan-mode: It refers to reader's automatic working mode.

## INTERFACE



## CHARACTERISTICS

- Absolute Maximum Rating

ITEM	SYMBOL	VALUE	UNIT
Power Supply	VCC	12	V
Operating Temp.	T <sub>OPR</sub>	-10~+60	°C
Storage Temp.	T <sub>STR</sub>	-25~+80	°C

- Electrical and Mechanical Specification

Under T<sub>A</sub>=25 °C VCC=+12V unless specified

ITEM	SYMBOL	MIN	TYP	MAX	UNIT
Power Supply	VCC	11.5	12	15	V
Current Dissipation	I <sub>C</sub>		150	200	mA
Frequency	F <sub>REQ</sub>		13.56		MHz
Effective Distance*	DIS	0	80	100	mm

\*Effective distance depends on tag and working environment.

Remark: 1. Specifications are subject to change, please pay attention to our latest one.

2. Smart Identify Co., Ltd. reserves the right to the final interpretation of the above terms.