Smart Identify
Smart choice you choose

UHF Metal Tag

MT-P852011

RF Specification

Frequency	:	865~868MHz. or 902~928MHz.
IC Type	:	Impinj M4QT ,or Alien H3
Memory	:	M4QT:EPC 128bits,User 496bits ; H3:EPC 96bits,User 512bits
Read range (m)	:	On metal, Fixed reader(EIRP= 4W) : over than 4m; And Alien handheld reader: over than 2.5m

Application

- Any on metal or off metal items that can put the tags

Physical and Environmental Specifications

Material	:	ABS or PC
Size	:	85 x 20 x 11mm
Operating Temperature	:	-25 ^{0}C to + 55 ^{0}C
Ambient Temperature	:	-40 ^{0}C to + 85 ^{0}C
IP Rate	:	IP68
Temperature Shock test	:	Pass : from -20 degree to 70 degree , 6 Hour per circle
Solvent Test	:	95% Alcohol test pass #92 Gasoline test pass
Drop Test	:	Pass : 200 time from 1m.
RoHS	:	Compatible

Optional

- Pre-encoding
- Silk printing
- Laser printing

Attachment

- Screw
- Rivet
- AB glue
- Tie
- tape

Smart identify Ltd.
594/9 Hathairat Road, Bangchan Klongsamwa, Bangkok 10510 Thailand
Tel : +66(0)2-136-9171 to 4 Fax : +66(0)-136-9175

www.smartiden.com
smartidentify
@smartidentify