

# iData 70 mobile computer

# iData 70 Mobile Computer

More durable and stable operation

# Working more efficiently through extremely speedy data collection

The latest industry-level scanning engine ensures high sensitivity and accuracy. Streamlined systematic data collection process results in an increased scanning speed. Scanning and verification can be done in one step thanks to the new design of ergonomic scanning angle.



Data collection with NFC, GPS positioning, high-definition

camera or by other means is supported, so as to enable professional, precise and efficient collection of business data.

## Data transmission becoming more efficient and timely

Seamless network selection and connection according to needs with 4G wireless communication supported by all network operators helps to realize more efficient business data connection and communication.

The 5th generation Wi-Fi technology (802.11ac) is used to increase the transmission speed by 300%, enable free switch and transmission between two channel frequencies, and make the signal stronger and more stable.

Bluetooth 4.0 transmission technology features low power consumption and fast connection, perfectly matched with mainstream portable printers.

# Long-life battery supporting full-day operations

5000mAh li-polymer safe battery is used to support full-loaded operations of up to 24 hours.

The use of low-energy-consuming chipset and optimized system result in more efficient and less energy-consuming operations.

Fast recharging technology is adopted to shorten the recharging time by 40% and further extend the battery life.

www.smartiden.com
smartidentify
@smartidentify



# iData 70 mobile computer

#### **System Configuration**

CPU	High-performance quad-core 1.3 GHz processor
Operating System	Android 6.0
Memory	16GB ROM + 2GB RAM
Expansion Slot	Micro SD card, up to 32GB
Display	4 inch, 800 x480
Touch Panel	Industrial-grade capacitive panel
Camera (optional)	8 MXP autofocus camera in the back side, autofocus lens, LED flash
Exit Window	Corning Gorilla glass
Keypad	20 front keys, 4 side keys
Battery	3.8V 5000mAh rechargeable lithium polymer battery
Audio	Built-in microphone/Micro USB
Notification	Vibrator alerts/LED/Audio notification
Vibration Motor	Built-in programmable vibration motor

#### **Structural Parameters**

Dimensions	159x71x20 mm
Weight	262g (battery included)

#### **Communication Transmission**

Network Frequency	GSM 900/1800/1900MHz, CDMA BC0 (800MHZ),
	WCDMA band 1/2, TD-SCDMA band 34/39,
	TDD-LTE band 38/39/40/41, FDD-LTE band 1/3/7/8/20
Data Service	GPRS/EDGE/EVDO/HSPA+/TD-SCDMA/TDD-LTE/FDD-LTE
Wireless LAN	(Optional) Wi-Fi 802.11a/b/g/n
	(Optional) Wi-Fi 802.11a/b/g/n/ac
Bluetooth	Bluetooth 4.0 + EDR, Supporting BLE
GPS	Supporting GPS/AGPS/Glonass

#### **Operating Environment**

Development Tools	Android SDK+ JDK+Eclipse
Programming Language	Java
Operating Temp	-10°C ~ 50°C (14°F to 122°F)
Storage Temp	-20°C ~ 60°C (-4°F to 140°F)
Relative Humidity	0 ~ 95% (non-condensing)
Drop Specification	1.5-meter drops to concrete ground
Sealing	IP65
Electrostatic Discharge	Conforms to $\pm 15$ kV air discharge, $\pm 8$ kV direct discharge

#### **1D Laser Scanner**

**Optical Resolution** Scan Depth of Field Scan Angle Scan Speed

 $\geq$  4mil 3.81cm - 60.98cm 47° ± 3°(Standard) 102 ± 12 scans/sec. (Bidirectional)

## 1D / 2D Area Imager

**Optical Resolution** Scan Angle Scan Speed

#### NFC (Optional)

Frequency Reading Distance Protocol

13.56 MHz Within 10 mm ISO14443A/14443B/15693

## Input / Output Ports

USB Port Charger Port 1 (Micro USB port) 1

≥ 3mil

Omnidirectional

300 scans/sec.

## Accessories

Standard Optional

Battery, Hand strap, Wrist strap USB cable, Power adapter, Charging stand, Battery case,4-slot cradle, Silicon case

#### **Applications:**

Smart

Retail





Pharmaceutical

Asset



Smart

Supervision Management Transportation Enforcement

Smart Identify Ltd. 594/9 Hathairat Rd., Bangchan, Klong Samwa, Bangkok 10510 Thailand Tel:+66(0)2-136-9171-4 Fax:+66(0)2-136-9171

www.smartiden.com

- **f** smartidentify
- @smartidentify